

# PULSAR 255 AC/DC



AWS E6013  
AWS E7018  
AWS E308  
AWS A5.15



## Optional



cod. 90330



cod. 88031



$\varnothing 1,6 \text{ mm}$   
25 pz - cod. 90468  
 $\varnothing 2,0 \text{ mm}$   
25 pz - cod. 90470  
50 pz - cod. 90480  
 $\varnothing 2,5 \text{ mm}$   
25 pz - cod. 90471  
50 pz - cod. 90481  
 $\varnothing 3,2 \text{ mm}$   
15 pz - cod. 90490



$\varnothing 2,0 \text{ mm}$   
402 pz - cod. 90731  
 $\varnothing 2,5 \text{ mm}$   
303 pz - cod. 90745  
 $\varnothing 3,2 \text{ mm}$   
155 pz - cod. 90755



cod. 90361  
LCD DISPLAY DIN11 + GLASS DIN11



cod. 90385  
HELMET 2000 E11  
LCD DIN11  
cod. 90390  
HELMET 2000 E  
LCD DIN9-13

Technical specifications														
	CODE	Input voltage	Absorbed power	No load voltage	Welding current	X <sub>m</sub> /I <sub>a</sub> [A] EN 60974-1	X <sub>20°C</sub>	Electrodes (mm)	Box volume	Box weight	Box size (mm)	PCS per Euro pallet	Bar code	
PULSAR 255 AC/DC	42490	230V~1ph 50-60Hz	6	AC 47-51 DC 54-60	AC 55-200 DC 45-170	AC 10/200 DC 8/170	200A@20% AC 170A@20% DC	1,6-5	0,084m <sup>3</sup>	31	600x300x440	1	16	8004386424902
PULSAR 255 AC/DC ME	42499	230V~1ph 60Hz	6	AC 46-60 DC 48-62	AC 40-200 DC 40-160	AC 25/200 DC 25/160	200A@30% AC 160A@30% DC	1,6-5	0,084m <sup>3</sup>	31	600x300x440	1	16	8004386424995